NEC/MITSUBISHI
NEC-MITSUBISHI ELECTRONICS DISPLAY

NEC AccuSync® LCD71VM

- Allround LCD monitor with TN+film TFT display
- Slim bezel design
- Stable and excellent picture quality with (Non-Touch-Auto-Adjustment)
- Integrated speakers (2 x 1 W)
- Cable Management
- Low power consumption
- Rapid Response technology
- Versatile installation (VESA standard)
- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2

see more.

NEC AccuSync® LCD71VM

Panel Technology	TN+ film TFT
Screen Size [inch/cm]	17/43
Pixel Pitch [mm]	0.264
Viewing Angle	140° horizontal / 120° vertical (typ. at contrast ratio 10:1) 160° horizontal / 140° vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	450:1
Brightness (typ.) [cd/m^2]	250
Response Time (typ.) [msec]	16 (2 white / black; 14 black / white)
Colours [million]	16.2
Horizontal Frequency [kHz]	31.5-81.1
Vertical Frequency [Hz]	56-75
Optimum Resolution	1280 x 1024 at 60 Hz
Other Resolutions	1152 x 768; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Colour Temperature Control; Fine Adjust (analogue); Brightness; Intelligent Power Management, Contrast; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Manager (OSM) lock-out; Volume
Safety and Ergonomics	CE; Energy Star; FCC Class B; ISO 13406-2 (Pixel Failure Cass II); PCBC/B-mark; PCT Gost; TCO99, TÜV ERGONOMIE; TÜV GS; UL/C-UL or CSA; MPR II/ MPR III
Power Requirements on Mode [W]	36 (typ.)
Power Requirements Power-saving Mode [W]	3
Power Supply	100-120 V/220-240 V; 0.75 A/0.4 A; integrated power supply
VESA Mounting [mm]	100 x 100
Dimensions (W x H x D) [mm]	379 x 383 x 193
Screen Tilt [°]	-5 to +30
Bezel Width [mm]	19.6
Cable Management	yes
Kensington Lock	yes
Weight [kg]	4.6
Specials	Rapid Response; NaViSet™ and NaViSet™ Administrator compatible
Audio Functions	2 x 1 W integrated speakers
Colour Versions	Silver Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable VGA-VGA; CD-ROM; Sales Office List; Manual
Warranty	3 years warranty including backlight; 3 years on-site warranty within EU countries, Switzerland, Norway, Liechtenstein and Iceland; with optional exchange or repair and return service

NaViSet™ NaViSet™ Administrator

ISO 13406-2

LCD71VM-UK-07/04

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. July 2004